


Patent number: EP1036295
Publication date: 2000-09-20
Inventor: HAMERT JEAN-MARIE (FR); CASTIGLIONI ANTONIO (IT)
Applicant: DIETRICH & CIE DE (FR); ICOSS S R L (IT)
Classification:
- **International:** B01J19/00; B01J19/02; B01J19/18; F28D9/00; B01J19/00; B01J19/02; B01J19/18; F28D9/00; (IPC1-7): F28D9/00
- **European:** B01J19/00B2; B01J19/00D2; B01J19/02; B01J19/18; F28D9/00B; F28D9/00F
Application number: EP19980956969 19981127
Priority number(s): WO1998FR02550 19981127; FR19970015355 19971202

[Report a data error here](#)

Abstract not available for EP1036295

Abstract of corresponding document: **US6460614**

The heat exchanger according to the invention consists of two flat or slightly incurved parallel surfaces formed in two sheets of metal (2) and (3). The longitudinal edge pieces (8) and (9) and transverse edge pieces (12) and (13) have rounded edges. The entire exterior surface is coated with enamel. These exchangers may be used in groups of several parallel units arranged inside a tubular body, or they may be disposed in a radiating pattern inside a cylindrical tank in a chemical reactor, forming a complex exchanger. This invention is of interest to manufacturers of industrial heat exchangers, particularly exchangers designed for the chemical, pharmaceutical or agricultural/food industries.



Data supplied from the esp@cenet database - Worldwide